

PERFORMANCE CHEMICALS

SABIC® EPDM 657

Ethylene Propylene Diene Rubber

PRODUCT DESCRIPTION:

SABIC® EPDM 657 is high ethylene and medium ENB grade produced by solution polymerization using metallocene catalyst. This product is available in pellet form.

CHARACTERISTICS:

Compared to typical narrow MWD grades SABIC® EPDM 657 is designed for:

- Better physical properties
- Improved mixing and mill handling
- Improved extrusion characteristics

SABIC® EPDM 657 is designed for good physical properties, improved mixing, mill handling and extrusion compared to typical narrow MWD grades

TYPICAL APPLICATIONS:

- Hoses
- Mechanical goods
- Extruded profiles

TYPICAL DATA:



PROPERTIES	Unit	Value ⁽¹⁾	Test Method
Mooney Viscosity (ML 1+4, 125 °C)	MU	60	ASTM-D 1646
Ethylene Content	Wt%	73	ASTM-D 3900
Ethylidenenorbornene (ENB) Content	Wt%	5	ASTM-D 6047

(1) Typical values; not to be construed as specification limits.

DISCLAIMER: Products referred to in this document are sold subject to SABIC's Standard Terms and Conditions of Sale (the "Terms") which are available upon request. The information contained herein is supported by research and is believed to be reliable as of the date compiled and representative of production but no guarantee, representation or warranty, express or implied, is made or intended as to the correctness, sufficiency, suitability, merchantability or fitness for a particular purpose of any such information or the products to which it relates. Users are solely responsible for making their own determination as to the suitability of any product for their intended use and that such use is in compliance with applicable laws and standards. Nothing in this document is intended or should be construed to grant a license or immunity under any SABIC or third party intellectual property rights. Save and as expressly set out in the Terms, SABIC shall in no event be liable for any loss, damage or injury howsoever arising from the use of information or the products referred to herein.